

Desk/2600

Simplicity at the heart of countertop payment



- ▶ All payment methods accepted. Optimized for seamless contactless payment
- ▶ Save counter space and speed up the checkout process by pairing with the Desk/1600 PIN Pad
- ▶ Connect any wired devices through the single MagicBox cable enabling a unified integration
- ▶ Ensure business continuity with a battery back-up



TETRA



With its nimble design, the Desk/2600 fits perfectly on any counter.

Optimized checkout time

- Multiple alternative payment methods supported
- Highlighted contactless zone
- Large keypad and display
- Paired with the Desk/1600, saving space and speeding up the checkout

Seamless integration with wired POS device

MagicBox cable offering various wired connectivity including customer module for the Desk/1600

Maximized network availability

- Ethernet, Wi-Fi and 4G/GPRS with dual SIM
- Battery back-up to cover power loss

Highest security

- PCI PTS v6
- Optional PCI compliant privacy shield
- Highest physical protection of sensitive data thanks to TETRA vault design



| | | | |
|------------------------------|---|--|------------------|
| Processor | • Application & Crypto processor | • Cortex 32bit - 160 Mhz | • |
| Memory | • Internal | • 256 MB Flash, 256 MB RAM | • |
| OS | | • Telium TETRA | • |
| Card Reader(s) | • Magnetic card reader • Smart Card • Contactless | • ISO 1/2/3, 500K reads lifespan • EMV L1, 500K reads lifespan • EMV Contactless L1 3.0 spec compliant | • • • |
| Display | | • 2.8" backlight, glass lens, QVGA (320x240 pixels) | • |
| Keypad | • Physical keys | • 15 keys, raised markings, backlit • 4 function keys | • • |
| Audio | • Buzzer | | • |
| Terminal connectivity | • WAN | • WIFI w. WPS easy pairing • 4G / GPRS - Cat1-bis and Cat-M | Option Option |

| | | | |
|---|---|---|--|
| Terminal Connections | • USB | • USB-C | • |
| Terminal Connections via Accessories | • Magic Box | • USB-C (device) • USB-C (power) • Ethernet (RJ45) • USB-B (slave) • USB-A (host) • USB-A (option) | Option Option Option Option Option Option |
| | • USB peripherals | • RS-232 converter • PSTN modem | Option Option |
| Terminal Size | • Terminal full option without PINshield | • 180.2x83.2x43 mm (7.09x3.27x1.69") | • |
| Terminal Weight | • Terminal only | • 320g (11.29oz) | • |
| Environment | • Operating temperature • Storage temperature • Relative humidity | • 0 to +45°C (32°F to 113°F) • -20 to +70°C (-4°F to 131°F) • 85% HR at +40°C (104°F) | • • • |
| Security | • PCI PTS • Privacy shield | • PCI PTS V6 compliant • PCI compliant (factory mounted) | • Option |



www.ingenico.com

ingenico