

Lane/3600

Fast, secure and compact PIN Pad solution

- ▶ Ensure best-in-class transaction flow with an extensive contactless zone
- ▶ Integrate easily with your retail environment thanks to its compact size and wide range of accessories such as standpole and kiosk adaptation plate
- ▶ Provide a user-friendly, compact terminal for easy self-checkout



ingenico



With its compact design, the Lane/3600 fits perfectly in any retail or hospitality environment.

- Optimized for payment**
 All payment methods accepted, one easy-to-identify contactless reader.
- Designed for an intensive use in retail**
 - Powerful processing to increase transaction speed
 - Boosted memory (Up to 512MB RAM 512MB FLASH)
 - High speed processor (Cortex A7)
- Robust device for demanding retail environment**
 - Display with glass lens
 - High-performance card & swipe insertion.
- Easy integration into semi-attended kiosks**
 With optimized dimension and adaptation plate.
- Rear and fast QR code reader integrated camera**
 - Full-integrated 0.3MP rear camera
- Highest security**
 - PCI PTS v6
 - Optional PCI compliant privacy shield
 - Detection of abnormal cable's removal to alert and up to inhibit the terminal in case of threats
 - Anti-theft Kensington lock

Processor	<ul style="list-style-type: none"> • Application & Crypto processor 	<ul style="list-style-type: none"> • Cortex A7 	•	Terminal Connections	<ul style="list-style-type: none"> • HDMI 	<ul style="list-style-type: none"> • IDMI 	•
Memory	<ul style="list-style-type: none"> • Internal 	<ul style="list-style-type: none"> • 256 MB Flash, 128 MB RAM • 256 MB Flash, 256 MB RAM • 512 MB Flash, 512 MB RAM 	Option • Option	Terminal Connections via Accessories	<ul style="list-style-type: none"> • USB • Serial • Powered USB • Powered RS 232 • External Power Supply 	<ul style="list-style-type: none"> • USB Host • USB Slave • 1 RS232 • 12 V (USB retail) • 12 V 	• Option
OS		<ul style="list-style-type: none"> • Telium TETRA 		Stand Mounting	<ul style="list-style-type: none"> • Universal Payment Mount 		Option
SAM	<ul style="list-style-type: none"> • SAM slots 	<ul style="list-style-type: none"> • 1 	•	Privacy PIN shield	<ul style="list-style-type: none"> • Standard privacy shield 	<ul style="list-style-type: none"> • PCI compliant (factory mounted) 	Option
Card Reader(s)	<ul style="list-style-type: none"> • Magnetic card reader • Smart Card • Contactless 	<ul style="list-style-type: none"> • ISO 1/2/3 (500K reads lifespan bi-directional swiping) • EMV L1 (500K reads lifespan) • EMV Contactless L1 3.0 spec compliant 	• • •	Color customisation	<ul style="list-style-type: none"> • Rear casing 		Option
Integrated Camera		<ul style="list-style-type: none"> • 2M pixels, autofocus • 0,3M pixels (QR code library embedded) 	• Option	Terminal Size	<ul style="list-style-type: none"> • Terminal only 	<ul style="list-style-type: none"> • By standard white or black 	•
Display		<ul style="list-style-type: none"> • 2.8"backlight, glass lens, QVGA (320x240 pixels) 	•	Terminal Weight	<ul style="list-style-type: none"> • Terminal full option without PINshield 	<ul style="list-style-type: none"> • 227g (8oz) 	•
Touchscreen	<ul style="list-style-type: none"> • Capacitive 	<ul style="list-style-type: none"> • Finger (1000K lifespan signature) 	•	Environment	<ul style="list-style-type: none"> • Operating temperature • Storage temperature • Relative humidity 	<ul style="list-style-type: none"> • 0 to +50°C (32°F to 122°F) • -20 to +70°C (-4°F to 158°F) • 85% HR at +40°C (104°F) 	• • •
Keypad	<ul style="list-style-type: none"> • Physical keys 	<ul style="list-style-type: none"> • 15 keys, raised markings, backlit • 4 function keys (non-touch version) • Laser etched 	• Option Option	Security	<ul style="list-style-type: none"> • PCI PTS • Anti-removal • Anti-theft 	<ul style="list-style-type: none"> • PCI PTS V6 compliant • Active connector removal • Kensington lock receptacle 	• • •
Audio	<ul style="list-style-type: none"> • Buzzer • Audio Jack • Speaker 	<ul style="list-style-type: none"> • Stereo • Mono 	• Option Option				

