

ingenico

SELF/4000 LE

Compact, engaging and scalable all-in-one payment solution for your self-service indoor and outdoor kiosks



- Accept all payment methods including magstripe, EMV and NFC/Contactless and QR codes
- Easily integrate cashless payment in self-service indoor kiosks
- Offer the best-in-class self-service solution with color screen, camera, sound alerts and ADA friendly features
- Simplify solution integration, operation and scalability



With Self/4000 LE, easily integrate cashless payment in self-service kiosks.

All methods of payment accepted including QR-code based payment

Ruggedized:

- Designed for intensive use cases: IK09
- Indoor
- Qualified outdoor within the limits of IP44

Easy integration into a kiosk from the front or from the rear

Low Energy platform, showcasing faster boot times and a deep sleep mode for optimized performance

Highest level of security with PCI PTS v6 certification

Modularity:

- Add-on boxes to build the desired configurations (Power, MDB, EXE, Wireless)
- Upgradeable in the field

Ergonomic interface:

- Easy-to-use customer interface thanks to a simple UI
- Mechanical backlit keyboard for PIN entry and color display



Supported by Ingenic's suite of services

- Estate management & security solutions
- Hardware services
- Professional services

Specifications

Processor/OS	<ul style="list-style-type: none"> • Low energy platform • Telium TETRA 	✓	Terminal connectivity	<ul style="list-style-type: none"> • Ethernet 10/100, 1 x RJ45 LAN port • 4G 	✓ Option
Memory	<ul style="list-style-type: none"> • 512 MB Flash, 512 MB RAM • MicroSD up to 32GB 	✓ ✓	Security	<ul style="list-style-type: none"> • PCI PTS v6 certified 	✓
Contactless reader	<ul style="list-style-type: none"> • EMV Contactless L1 3.1 certified / Support ISO 14443 	✓	IP	<ul style="list-style-type: none"> • IP 44 	✓
Contact reader	<ul style="list-style-type: none"> • Hybrid card reader with shutter • RGB LEDs in reader's entry mouth • Smart card – EMV L1 – 500k reads lifespan • MSR ISO 1/2/3 – 500k reads lifespan 	✓ ✓ ✓ ✓	IK	<ul style="list-style-type: none"> • IK 09 	✓
SAM	<ul style="list-style-type: none"> • 2xSAM ID-000 	✓	Power supply	<ul style="list-style-type: none"> • 9-16 V DC (light sleep mode) • 10-45V DC with optional Add-on box • Deep sleep mode for low consumption 	✓ Option ✓
Display	<ul style="list-style-type: none"> • 2.27" color IPS – 640 x 240 • Wide angle viewing (+/- 180°) 	✓	Terminal size	<ul style="list-style-type: none"> • EVA EPS – Standard Door Module • 3.3 (W) x 4.2 (H) x 4.3 (D) in. (85x107.2x109.6 mm) 	✓ ✓
Keypad	<ul style="list-style-type: none"> • Mechanical 16 backlit keys keyboard 	✓	Weight	<ul style="list-style-type: none"> • 22 oz (620 g) 	✓
Audio	<ul style="list-style-type: none"> • Buzzer Monotone • Wav sound (thru external speaker) 	✓ ✓	Environment	<ul style="list-style-type: none"> • -4°F to 158°F (-20°C to +70°C) – Operating • -4°F to 158°F (-20°C to +70°C) – Storage • 95% non-condensing at +131°F (55°C) 	✓ ✓ ✓
Camera	<ul style="list-style-type: none"> • 2MP – fixed focal (Honeywell library embedded) 	Option	Mounting in the kiosk	<ul style="list-style-type: none"> • From outside without EVA plate • From inside with EVA plate 	✓ ✓
Terminal connections	<ul style="list-style-type: none"> • 1 x USB Slave • 2 x USB Host • 2 x RS232 • 1 x connector for external loudspeaker • 1 x MDB Master + 1 x MDB Slave 	✓ ✓ ✓ ✓ Option	Accessory	<ul style="list-style-type: none"> • Adapter cable for standard 12V PSU • EVA EPS mounting steel plate • USB cables, serial cables... • PSU 12V DC... 	✓ ✓ Option Option
			Add-on boxes	<ul style="list-style-type: none"> • POWER add-on box (slot#1) • MDB or EXE add-on box (slot#2) • 4G add-on box (slot#2) 	Option Option Option

