

# **AXIUM SX5000**

Unleashing Android innovation for an enhanced self-service checkout





certification

The AXIUM SX series delivers outstanding performance, reliability, versatile configurations, and an enriched user interface, opening the door to limitless possibilities.

### The power of Android. Harness the power of the Appstore.

### Ergonomic and elegant device for a smooth consumer experience

- · Large full touch display
- Presence & luminosity sensors
- User-Friendly QR Code Scanning
- Smartphone-Like interface thanks to Android

#### Support contactless and QR-code based payment, PIN on Glass certified.

### Ruggedized

- · Designed for intensive use cases: IK09
- Indoor or outdoor: IP65
- Outdoor certified

#### **Effortless integration:**

- · Frontal integration facilitated by an internally mounted plate and low depth at the back for simplified incorporation in any kiosk
- Compliant with EVA EPS (Standard Door Module)

## Versatile communication and connectivity options:

· A full set of connectivity and connections (including USB, RS232, MDB, multimedia interface for external screen, Ethernet, WiFi, Bluetooth and 4G) covering most kiosk system requirements

### Highest level of security with PCI PTS certification.

## **Specifications**

Processor	Application processor     Crypto processor	Cortex Quad-core A53, 2GHz     Security core M33, 160MHz	~
Memory	• Internal	16GB Flash, 2GB RAM     32GB Flash, 4GB RAM	Option
os	Android	Android 14 Security OS	~
Card readers	Contactless	EMV Contactless L1 3.x compliant; support ISO / IEC 14443 Type A / B / B'     Tap on screen, virtual	~
		contactless LEDs	
SAM	SAM slots	• 2 slots	~
Display & Touchscreen	Color / capacitive multi-touch	<ul><li>5" IPS, 720 x 1280 px</li><li>5mm glass thickness</li></ul>	ž
Keypad	Virtual screen keys	Menu, Home, Back	~
Sensors		Presence sensor     Luminosity sensor	× ×
Audio	Audio Jack     Buzzer	Headphone mini Jack at the back for external speaker     Buzzer monotone	<b>*</b>
Data capture	Downward facing camera and the Honeywell library embedded	0.3M pixels, fixed focus camera, for code scanning	~
Terminal mounting	From outside the kiosk		~

ingenico  we because  Large General ingenico  CHARGE STATUS  65%	THE ESTATE MANAGER  WORKEN CRUTENTY  Terminal diagnostic > 2167CU800221		Diagnostic List Sons			
	AXIUM S Signature Name merchant ID	5X5000 12Ab cd18-24 5X5000 - Paul 1256688		Contactless Camera Wifi	_ Ongoing _	l
			_	-		

1.1.								
Floot	ma	naa	aman	ı+ ς.	200	ı ıritv	دمار	tions

- Support services
- Professional services

Connectivity	<ul><li>Wired</li><li>Wireless</li></ul>	Ethernet 10/100 base T  WiFi IEEE802.11 a/b/g/n/ac 2.4G and 5G  Bluetooth 5.0, support BLE  4G (1 SIM slot)	y y Option
Connections		1USB-A Host     1USB-C Device     1RJ45 LAN     1RJ11 RS232     1MDB 4.3 Slave     1HDMI* port     1/O isolated ports (2 inputs, 2 outputs)	· · · · · · · · · · · · · · · · · · ·
Power supply		• 9-45V DC	~
Size	Overall W x H x D mm  Installation cutout EVA EPS v2	<ul> <li>110 x 146 x 57.65 mm         (4.3 x 5.7 x 2.3")         (31.5mm front protrusion, 26.15mm kiosk depth)         104.5 x 81 mm         (26.15 mm deep)     </li> </ul>	~ ~
		Standard Door Module	~
Weight		• 532g (18.7oz)	~
Security	• PCI	PCI PTS V6 certified	~
Ruggedized	Outdoor certified	CE Outdoor	~
IP	Ingress protection	• IP65	~
IK	Shock protection	• IKO9	~
Environment	Operating T°     Storage T°     Operating     Humidity	<ul> <li>-20°C to +65°C (-4°F to 149°F)</li> <li>-25°C to +70°C (-3°F to 158°F)</li> <li>up to 95% HR at +55°C (+131°F), non condensing</li> </ul>	· · · ·
Accessories	EVA EPS     Cables     PSU     MDB box	Mounting plate USB cables, SERIAL cables 12V DC MDB Master + MDB Slave + Simple EXE + Double EXE + Audit + 2 x USB-A host	Option Option Option

\* The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

